



Precision-V No-Clean Flux Remover

1649

Flux removers (defluxers) remove flux residues and other contaminants left by manufacture, rework, or repair of printed circuit boards. Residues from higher, leadfree temperatures are more baked on and harder to clean. Techspray flux removers have been proven very effective at removing fluxes baked on at leadfree temperatures.



[Request More Info](#)



Non-flammable, powerful enough for the toughest no-clean fluxes

Innovative cleaning technology that blasts away the toughest no-clean flux without leaving the dreaded white residues! As fluxes are reformulated to meet modern production, performance and environmental requirements, current cleaning methods become less effective. Tried and true processes can suddenly produce unsightly residues and potentially product failures.

Precision-V No-Clean Flux Remover is a proprietary blend of solvents to remove no-clean, rosin and even aqueous OA fluxes. Precision-V No-Clean is non-flammable and non-ozone depleting, so an ideal replacement for AK225-based cleaners.

- Effective on toughest flux residues
- Non-flammable
- Non-ozone depleting
- Rapid evaporation with no residue
- Safe on most plastics

Product Packaging

1649-12S
Precision-V No-Clean Flux Remover
 12 oz
 12 units/case



Techspray
 8125 Cobb Center Drive,
 Kennesaw, GA 30152
 800-858-4043 • www.techspray.com



Technical Information

Plastics & Rubber Compatibility

MATERIAL NAME	RATING
Black ABS	Not recommended
Nylon 6	Compatible
Nylon 6/6	Compatible
Polycarbonate	Not recommended
HDPE	Compatible
LDPE	Compatible
C.E. Phenolic	Compatible
PMMA	Not recommended
POM	Compatible
PP	Compatible
PS	Not recommended
PTFF	Compatible
PVC (plasticized)	Compatible
PVC (rigid)	Compatible

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
Email: tsales@techspray.com

Europe

ITW Contamination Control
Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
Email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country.



Techspray
8125 Cobb Center Drive,
Kennesaw, GA 30152
800-858-4043 • www.techspray.com



Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

© 2017 Techspray, A Division of ITW